

Gengear Series

Heavy Duty Industrial Gear Lubricants

Description

A range of heavy duty industrial gear lubricants made from high quality paraffinic mineral oils, incorporating unleaded additives to provide extreme pressure and anti-wear characteristics, rust and corrosion protection, enhanced oxidation stability and resistance to foaming. These oils have friction modifying characteristics that reduce power consumption and lower bulk oil temperatures. They have Timken OK Load ratings of 27 kilograms.

Application

Gengear oils are recommended for industrial enclosed gear sets with circulation or splash lubrication systems operating at no more than 110 °C bulk oil temperature. For worm gears operating at bulk temperatures above 95 °C, Gengear SPL PG-Series is recommended. Non-gear applications for Gengear oils include shaft couplings, screws and heavily loaded bearings operating at slow speeds. See also Gengear XEP Series.

Benefits

- Outstanding antiwear properties.
- Good oxidation stability.
- Good rust and corrosion protection.
- Good demulsibility.
- Excellent anti-foam characteristics.
- Good filterability.

Typical Physical Characteristics

Gengear	68	100	150	220	320	460	680
Viscosity, cSt @ 40 °C	65	100	140	210	305	440	650
Viscosity, cSt @ 100 °C	8,6	11,3	14,5	18,3	23,3	30,0	36,0
Viscosity Index, min.	95	95	95	95	95	95	80
Flash Point, °C min.	204	208	210	216	232	232	232
Pour Point, °C max.	-24	-24	-24	-18	-15	-6	-6
Neutralization No., max.	1,5	1,5	1,5	1,5	1,5	1,5	1,5
FZG, Stages Passed	>12	>12	>12	>12	>12	>12	>12
AGMA No.	2EP	3EP	4EP	5EP	6EP	7EP	8EP
ISO VG	68	100	150	220	320	460	680

02.2015

Due to continual product research and development, the information contained herein is subject to change without notification. Refer to the Material Safety Data Sheet (MSDS) for information on the safe handling and use of this product.

Engen Petroleum Ltd | Tel: 08600 36436 | Website: www.engenoil.com | Email: 1call@engenoil.com