

Engen Readymix Coolant

Premixed Engine Coolant Based on Ethylene Glycol

Description

Engen Readymix Coolant is a nitrite-, amine-, silicate-, borate- and phosphate-free premixed engine coolant based on ethylene glycol. Being pre-diluted with deionized and demineralized water and ready for use there is no chance of over or under dosing. It provides excellent corrosion protection to all cooling system metals and alloys used in internal combustion engines. It provides protection against freezing down to -10 °C for up to one year. It is miscible with most other conventional coolants, although mixing is not recommended.

Application

Engen Readymix Coolant is designed for the DIY enthusiast and is ready to use (no water must be added). It can be used as a coolant in all water-cooled internal combustion engines to protect against corrosion and frost damage. It is strongly recommended that the cooling system be drained completely and flushed with clean water before being filled with a fresh charge of antifreeze mixture.

Warning: Harmful if swallowed. Keep out of the reach of children.

Performance Level

BS 6580 and ASTM D 3306

Benefits

- Guards against rust and corrosion.
- Can provide protection against winter freezing down to -10 °C.
- Protects all cooling system metals including aluminium.
- Suitable for all water cooled petrol and diesel engines.
- Improves summer cooling by promoting rapid heat transfer

Typical Physical Characteristics

Engen Readymix Coolant	
Density @ 20 °C kg/l	1,05
Colour Luminous	Yellow
Freezing point, °C, min	-10

02.2015

Due to continual product research and development, the information contained herein is subject to change without notification. Refer to the Material Safety Data Sheet (MSDS) for information on the safe handling and use of this product.

Engen Petroleum Ltd | Tel: 08600 36436 | Website: www.engenoil.com | Email: 1call@engenoil.com